

**1. CONDUCTOR:**

- 1.1 Size and Material: 22 AWG, 7 strands, nickel-plated copper wire.
- 1.2 O.D.: .0285" nom.

**2. INSULATION:**

- 2.1 Extruded special ETFE (Tefzel® 750).
- 2.2 Wall thickness: .006" nom.
- 2.3 Marking on the insulation: not required as per UL and CSA Standards.
- 2.4 O.D.: .0405" nom.
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 300 VAC R.M.S.
- 3.2 Temperature rating: 200°C


**4. REFERENCES:**

- 4.1 UL Subject 758 (AWM), Style 10109.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Pierre Garand</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com		
								Date: June 16, 2015				
								Verified: <i>Carrie Holt</i>		Description: <b>XTL6N227/0096-X</b>		
								Date: June 16, 2015				
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.								Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F04835-X</b>