

UL 10109

200° C., 300 Volt



- A.** Center conductor - solid or stranded tin or silver plated copper¹
- B.** Insulation - extruded ETFE

Applications

Internal wiring of electrical equipment and UL classified appliance wire service up to 200° C.

Listings

200° C., 300 volt: UL10109; CSA: Class 1 Group A/B

| Catalog Number | Size (AWG) | Stranding (No./AWG) | Insulation Thickness (mils) | Overall Diameter (inches) | Weight (lbs/1000 ft) | Part Number | |
|----------------|------------|---------------------|-----------------------------|---------------------------|----------------------|-------------|--------|
| | | | | | | U.S. | Canada |
| TZ10109-301S | 30 | 1/30 | 6 | .022 | 1 | - | 2450 |
| TZ10109-307S | 30 | 7/38 | 6 | .024 | 1 | - | 2451 |
| TZ10109-281S | 28 | 1/28 | 6 | .025 | 1 | - | 2452 |
| TZ10109-287S | 28 | 7/36 | 6 | .027 | 1 | - | 2453 |
| TZ10109-2819S | 28 | 19/40 | 6 | .027 | 1 | - | 2454 |
| TZ10109-261T | 26 | 1/26 | 6 | .028 | 1 | - | 2455 |
| TZ10109-261S | 26 | 1/26 | 6 | .028 | 1 | - | 2456 |
| TZ10109-267S | 26 | 7/34 | 6 | .031 | 1 | - | 2457 |
| TZ10109-2619S | 26 | 19/38 | 6 | .031 | 1.5 | - | 2458 |
| TZ10109-241T | 24 | 1/24 | 6 | .032 | 2 | - | 2459 |
| TZ10109-241S | 24 | 1/24 | 6 | .032 | 2 | - | 2460 |
| TZ10109-247S | 24 | 7/32 | 6 | .036 | 2 | - | 2461 |
| TZ10109-2419S | 24 | 19/36 | 6 | .035 | 2 | - | 2462 |
| TZ10109-221T | 22 | 1/22 | 6 | .037 | 2.5 | - | 2463 |
| TZ10109-221S | 22 | 1/22 | 6 | .037 | 2.5 | - | 2464 |
| TZ10109-227S | 22 | 7/30 | 6 | .042 | 3 | - | 2465 |
| TZ10109-2219S | 22 | 19/34 | 6 | .042 | 3 | - | 2466 |
| TZ10109-201T | 20 | 1/20 | 6 | .044 | 4 | - | 2467 |
| TZ10109-201S | 20 | 1/20 | 6 | .044 | 4 | - | 2468 |
| TZ10109-207S | 20 | 7/28 | 6 | .050 | 4 | - | 2469 |
| TZ10109-2019S | 20 | 19/32 | 6 | .050 | 5 | - | 2470 |