

1. CONDUCTOR:

- 1.1 Size and Material: 18 16/30 AWG tin-plated copper wire.
- 1.2 O.D.: .045" nom.

2. INSULATION:

- 2.1 Extruded special ETFE (Tefzel® 750).
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .065" ± .002"
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 150°C






4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 10126.
- 4.2 CSA Standard C22.2 No.210.2 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.	 <p style="font-size: small;">This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: 	 <p style="font-size: x-small;">1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com</p>				
		Date: August 9, 2005					
		Verified: 	Description: XTL10Z1816/30-X				
		Date: August 9, 2005					
UNCONTROLLED DOCUMENT A later revision of this specification may exist.	 <p style="font-size: x-small;">A member of The Marmon Group of companies</p>	Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F02308-X	Rev. ---