


UL 1015 16AWG(1.31mm²) Single Wire



PRODUCT DATA SHEET

Internal Wiring of Appliances.



Design Number 10196
Part Number 1015/16Q26-1Z36
Customer Number N/A

CONSTRUCTION

Conductor: Stranded over coated bare copper
Conductor Size: 16AWG(26/30)
Insulation: Polyvinyl chloride (PVC)
Insulation Avg. Thickness: 0.030"(Nom.)
Insulated O.D.: 0.116"(Nom.)
Color: Red

Print Legend:

ASCENT E477982 CK AWM 1015 16AWG(1.31mm²) 105°C 600V
VW-1 --- c AWM I A/B 105°C 600V FT1 - LF -

Package: 1000 FT/Roll

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): 105°C
Operating Voltage: 600V
Conductor Resistance@20°C: 14.6 Ω/km Max
Dielectric Test: AC 2.0 kV/1 min
Flame Test : UL VW-1

SAFETY CHARACTERISTICS

RoHS Compliance: European Directive 2015/863/EU
Approvals: UL 758 , UL 1581 and AWM UL 1015

Application: Internal Wiring of Appliances

All trademarks are property of their respective owners. All specifications are subject to change.

| Revision History | | |
|------------------|-------------------|-----------------|
| 00 | 2020/01/07 | Initial release |
| | | |
| Created L. Jian | Approved A. Huang | |

Bristol | Unit 61, Gazelle Rd., Weston Industrial Estate, Weston-super-Mare, North Somerset BS24 9ES UK

Frankfurt | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf

Milwaukee | 5001 South Towne Dr. New Berlin, WI 53151 USA

Suzhou | B2-2 Weiting Town Industrial - Workshop A, No. 9 Weixin Rd., Suzhou Industrial Park, Jiangsu, China 215122

