



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 14-41 CU MTW/THHW/BC-5W2/TEW/AWM/1015

STOCK NUMBER: Various

CONDUCTOR:

NOMINAL OUTSIDE DIAMETER:	.136" +/- .002"	in.
NOMINAL WALL THICKNESS:	.030"	in.
INSULATION COMPOUND:	Polyvinyl Chloride	
COPPER:	14AWG 41x.010" SBC	

TEMPERATURE: 105°C - dry
75°C - wet

FILLERS: N/A

PRINT: **INK**
E51583 (M) 14 AWG (2.08mm²) (UL) MTW 600V or BC-5W2 or THHW or AWM STYLE 1011,1015,1230,1335
600V or 1032 1000V Moisture Resistant VW-1 LL90458 CSA TEW 105°C FT-1 or AWM I A/B
105°C 600V FT-1 (M) --- RoHs

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 1063 MACHINE - TOOL WIRES AND CABLES STANDARD - NO. E51583
CSA STANDARD C22.2 NO. 127 EQUIPMENT WIRES - NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013