



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 16-26 CU MTW/BC-5W2/TEW/AWM/1015/1032

STOCK NUMBER: Various

CONDUCTOR:

NOMINAL OUTSIDE DIAMETER:	.120" +/- .002"	in.
NOMINAL WALL THICKNESS:	.030"	in.
INSULATION COMPOUND:	Polyvinyl Chloride	
COPPER:	16AWG 26X.010" SBC	

TEMPERATURE: 105°C - dry
75°C - wet

FILLERS: N/A

PRINT: **INK**
E51583 (M) 16 AWG (1.31mm²) (UL) MTW 600V or BC-5W2 or AWM STYLE 1011,
1015,1230,1335 600V or 1032 1000V Moisture Resistant VW-1 LL90458 CSA TEW 105°C
FT-1 or AWM I A/B 105°C 600V FT-1 (M) — RoHs

PRODUCT MANUFACTURED IN ACCORDANCE TO:

*UL STANDARD NO. 1063 MACHINE - TOOL WIRES AND CABLES STANDARD - NO. E51583
CSA STANDARD C22.2 NO. 127 EQUIPMENT WIRES - NO. LL90458*

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013
