



ATLAS WIRE CORPORATION
 9525 RIVER STREET
 SCHILLER PARK, ILLINOIS 60176
 (847) 678-1210
 (847) 678-1281 FAX
 www.atlaswirecorp.com



Atlas Wire Corporation
 Registered to ISO9001 and TS16949
 Schiller Park, IL 60176
 Reference No. 10000854
 Tucson, AZ 85714
 Reference No. 10003647

MATERIAL SPECIFICATION SHEET

**#14 SOLID TC 1/32" PVC
 RoHS COMPLIANT**

**AWM STYLES 1015 & 1230 105c-600v
 AWM STYLE 1032 90c-1,000v AWM STYLES 1013/1335 90c-600v
 CSA TEW or AWM 1 A/B 105c-600v or CSA TR-32 90c
 CSA OIL AND WATER RESISTANT 75c FT1**

CONDUCTOR:	# 14 SOLID TINNED COPPER	
	APPROXIMATE NOMINAL O.D.	.0641"
	APPROXIMATE CIRCULAR MILL AREA	4,106
	WEIGHT PER THOUSAND FEET	12.55#
	BASIC SPECIFICATION	ASTM B 33
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	ELONGATION	330% AVG
	SPECIFIC GRAVITY	1.32
	DUROMETER (SHORE)	91 (A)
	TENSILE STRENGTH	2,450 PSI AVG
	OXYGEN INDEX	28
	BRITTLE POINT	-24c
	SPARK TESTED	10,000 VOLTS
	FINISHED O.D.	.127"
	WEIGHT PER THOUSAND FEET	18.20#
USE:	INTERNAL WIRING OF APPLIANCES; OR INTERNAL WIRING OF APPLIANCES WHERE EXPOSED TO OIL AT A TEMPERATURE NOT EXCEEDING 60c.	
UL1230,1335:	MOISTURE RATING 60c.	
UL1032:	3,500v PEAK FOR ELECTRONIC USE ONLY	
UL 1015,1013:	2,500v PEAK FOR ELECTRONIC USE ONLY	