



ATLAS WIRE LLC.
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001 and TS16949
Schiller Park, IL 60176
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#22 7/0096 BC 1/32" PVC

RoHS COMPLIANT

MACHINE TOOL WIRE 600v N.E.C. STANDARD

AWM STYLES 1015 & 1230 105c-600v AWM 1032 90c-1,000v OR

AWM 1013, 1011, 1335 90c-600v VW-1

**CSA TEW 105c-600v FT1 OR TR32 90c FT1 OR AWM I A/B 105c-600v
O & W75c FT1**

CONDUCTOR:	#22 7/0096 BARE COPPER 3/4" CONCENTRIC LAY	
	NOMINAL O.D.	.029"
	APPROXIMATE CIRCULAR MILL AREA	646
	WEIGHT PER THOUSAND FEET	2.0#
	BASIC SPECIFICATION	ASTM B 8 ASTM B 286
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	600v
	ELONGATION	330% AVERAGE
	TENSILE STRENGTH	2450 PSI AVERAGE
	SPECIFIC GRAVITY	1.32
	DUROMETER (SHORE)	91 (A)
	OXYGEN INDEX	28
	SPARK TESTED	10,000 VOLTS
	FINISHED O.D.	.091"
	WEIGHT PER THOUSAND FEET	5.51#
USE:	INTERNAL WIRING OF APPLIANCES; OR INTERNAL WIRING OF APPLIANCES WHERE EXPOSED TO OIL AT A TEMPERATURE NOT EXCEEDING 60c. CSA MOISTURE & OIL RESISTANT 75c. UL 1230, 1335 – MOISTURE RATING 60c UL 1011, 1013, 1015, 1335 – 2,500v PEAK FOR ELECTRONIC USE ONLY UL 1032 – 3,500v PEAK FOR ELECTRONIC USE ONLY	

info@atlaswirecorp.com

REVISION 5-24-2016

