



ATLAS WIRE LLC.
 9525 RIVER STREET
 SCHILLER PARK, ILLINOIS 60176
 (847) 678-1210
 (847) 678-1281 FAX
 www.atlaswirecorp.com



Atlas Wire Corporation
 Registered to ISO9001 and TS16949
 Schiller Park, IL 60176
 Reference No. 10000854
 Tucson, AZ 85714
 Reference No. 10003647

MATERIAL SPECIFICATION SHEET

**#10 19/0234 TC 1/32" PVC
 RoHS COMPLIANT**

**10 AWG. E25635 RU AWM 1015/1230 105C 600V OR
 AWM 1013/1335 90C 600V OR AWM STYLE 1032 90C 1000V VW-1
 CSA 150272 TR-32 90C FT1 OR TEW 105C 600V FT1 OR AWM I A/B
 105C 600V O W 75C FT-1**

CONDUCTOR:	#10 19/0234 TINNED COPPER 1 ½" UNILAY
	APPROXIMATE NOMINAL O.D. .116
	APPROXIMATE CIRCULAR MILL AREA 10,404
	WEIGHT PER THOUSAND FEET 32.02#
	BASIC SPECIFICATION ASTM B 8
	ASTM B 286
PVC:	TEMPERATURE RATING 105c
	VOLTAGE RATING 600 VOLTS
	ELONGATION 330% AVERAGE
	TENSILE STRENGTH 2450 PSI AVERAGE
	SPECIFIC GRAVITY 1.32
	DUROMETER (SHORE) 91 (A)
	OXYGEN INDEX 28
	BRITTLE POINT -24c
	SPARK TESTED 10,000 VOLTS
	FINISHED O.D. .178"
	WEIGHT PER THOUSAND FEET 40.63#
USE:	INTERNAL WIRING OF APPLIANCES; OR INTERNAL WIRING OF APPLIANCES WHERE EXPOSED TO OIL AT A TEMPERATURE NOT EXCEEDING 60c. UL 1230, 1335 – MOISTURE RATING 60c UL 1011,1013,1015,1335 – 2,500v PEAK FOR ELECTRONIC USE ONLY. UL 1032 – 3,500v PEAK FOR ELECTRONIC USE ONLY.

info@atlaswirecorp.com