


UL 1213 – 24AWG Teflon PTFE Wire



PRODUCT DATA SHEET

Internal wiring of appliances where exposed to oil at temperature not exceeding 60C.



Design Number 10321
Part Number Table 1
Customer Number N/A

CONSTRUCTION

Conductor: Stranded silver plated copper
Conductor Size: 24AWG(7/0.20mm)
Conductor Diameter: 0.61mm(Nom.)
Insulation Material: Extruded Polytetrafluoroethylene (PTFE)
Avg. Thickness: 0.26mm(Nom.)
Insulated Diameter: 1.13±0.10mm
Insulation Color: A variety of colors available

Print Legend:

E477982 CS AWM STYLE 1213 105°C VW-1 24AWG ROHS

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): -60°C to +200°C
Operating Voltage: 600V
Conductor Resistance@20°C: Max 86 Ω/km
Dielectric Test: AC 1.0 kV/1 min
Insulation Resistance@20°C: Min 200 MΩ.KM

SAFETY CHARACTERISTICS

RoHS Compliance: European Directive 2015/863/EU
Reference Standards: UL 758, UL 1581, and Style Page UL 1213
Approvals: AWM UL 1213

Table 1

Part Number	Insulation Color
32051695	Black
32051696	White
32051697	Blue
32051698	Red
32051699	Green

Application: Common applications include military harnessing power supply lead time, appliance wiring, and medical electronics.

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2020/11/17	Initial release
Created L. Jian	Approved A. Huang	

Bristol | Unit 61, Gazelle Rd., Weston Industrial Estate, Weston-super-Mare, North Somerset BS24 9ES UK
Frankfurt | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf
Milwaukee | 5001 South Towne Dr. New Berlin, WI 53151 USA
Suzhou | B2-2 Weiting Town Industrial - Workshop A, No. 9 Weixin Rd., Suzhou Industrial Park. Jiangsu, China 215122

