UL CMR/2464 22AWG/5C Gray



PRODUCT DATA SHEET

Cable is suitable for installation under NEC (NFPA 70) article 800 guidelines. Cable is suitable for installation in Canada under Section 60 of CEC, Part I. Internal wiring or external interconnection of electronic equipment.

Design Number10356Part Number32130972Customer NumberN/A

CONSTRUCTION

Conductor: Annealed Tinned Copper **Conductor Size:** 22AWG 7 Strands Class B

Insulation: Polyvinyl Chloride Insulation Thickness: 0.010"(Nom.) Insulation Diameter: 0.050"(Nom.)


Cable Lay Length: 2.00" LHL (6.0 tw/ft), Nom.

Jacket Material: Polyvinyl Chloride Jacket Thickness: 0.032"(Nom.) Overall Diameter: 0.199"(Nom.)

Jacket Color: Gray

Print Legend (Footage Markers):

ASCENT E478021 22AWG 5C 75C C(UL)US CMR SUN RES OR AWM 2464 300V 80C OR AWM 2576 150V 80C "ROHS COMPLIANT" MADE IN USA



Color Code: Black, White, Red, Green, Brown

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): 80°C Operating Voltage: 300V

Weight: 26 Lbs/Mft

SAFETY CHARACTERISTICS

C(UL)US listed as CMR per UL standard 444 and per CSA C22.2 No. 214-17 UL recognized component as AWM 2464 and AWM 2576 per UL standard 758 Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive

Cable is REACH compliant per Regulation (EC) No. 1907/2006 (240) Undated

Cable is REACH compliant per Regulation (EC) No 1907/2006 (240) Updated January 23, 2024

Application: Internal wiring or external interconnection of electronic equipment

All trademarks are property of their respective owners. All specifications are subject to change.

