U.I. Lapp GmbH

PRODUCT INFORMATION



EPIC® MC Module: 10pole

05.11.2015

The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and slide-in technology.

The mix of different functions in one plug guarantees high flexibility Assembly of individual connectors, suitable for different applications





Automation & fältinstallation



Industrial machinery and plant engineering



Wind Energy

Info

Ideal for data transmission

Application range

Plant engineering Printing machines Control engineering

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Rated voltage (V): 400 V
Rated current (A): max. 10 A
Contact resistance: < 2 mOhm

Contacts: Copper alloy, hard silver/gold-plated

Number of contacts: 10

Termination methods: Crimp termination: 0.14 - 2.5 mm²

Cycle of mechanical operation: 100

Temperature range: -40°C to +100°C, short-term up to +125°C

Degree of soiling: 3

Product Management	Document: LAPP_PRO816EN.pdf	1 / 3	

Document: LAPP_PRO816EN.pdf

2/3

Product Management

Part number	Article description		Number of operating contacts	Slots	Pieces / PU	
Module: 10-pin						
10382400	MCS 10 CM	male	10	1	10	
10382500	MCB 10 CM	female	10	1	10	

05.11.2015	EPIC® MC Module: 10pole	
M LAPP GROUP	PRODUCT INFORMATION	U.I. Lapp GmbH

U.I. Lapp GmbH	PRODUCT INFORMATION	EAPP GROUP
	EPIC® MC Module: 10pole	05.11.2015

