# PRODUCT INFORMATION



## EPIC® MC Module: High Voltage 3pole

05.11.2015

The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and slide-in technology.

The mix of different functions in one plug guarantees high flexibility Assembly of individual connectors, suitable for different applications





Automation & fältinstallation



Industrial machinery and plant engineering



Wind Energy

Info Very high current transfer in a small space

### **Application range**

Plant engineering Printing machines Control engineering

#### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

### **Technical Data**

	1000 \/
Rated voltage (V):	1000 V
Rated current (A):	50 A
Contact resistance:	< 2 mOhm
Contacts:	Copper alloy, hard silver-plated
Number of contacts:	3
Termination methods:	Crimp termination: 1.5 - 10 mm <sup>2</sup>
Cycle of mechanical operation:	100
Temperature range:	-40°C to +100°C, short-term up to +125°C
Degree of soiling:	3

Product Management	Document: LAPP_PRO812EN.pdf	1 / 3
PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved Photographs are not to scale and do not represent detailed images of the respective products.		



Part number	Article description	Contact type	Number of operating contacts	Slots	Pieces / PU
Module: high voltage 3-pin					
10399800	MCS 3 CM-HV	male	3	1	10
10399900	MCB 3 CM-HV	female	3	1	10

Product Management

Document: LAPP\_PRO812EN.pdf

EPIC® MC Module: High Voltage 3pole

PRODUCT INFORMATION

U.I. Lapp GmbH


05.11.2015


**® LAPP GROUP** 

	GROUP
EPIC® MC Module: High Voltage 3pole	

F







Product Management	Document: LAPP_PRO812EN.pdf	3 / 3
PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved Photographs are not to scale and do not represent detailed images of the respective products.		