

1. CONDUCTOR:

- 1.1 Size and Material: 6 AWG, 133 strands, tin-plated copper wire.
- 1.2 O.D.: .206" nom

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Wall thickness: .068" nom.
- 2.3 Marking on the insulation: as per UL Standard.
- 2.4 O.D.: .342" nom.
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 25 KVDC
- 3.2 Temperature rating: 150°C






4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 10475.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.	 <p style="font-size: small;">This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: 	 <p style="font-size: x-small;">1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com</p>				
		Date: March 2, 2011					
		Verified: 	Description: XSF68Z6133/27-X				
		Date: March 3, 2011					
UNCONTROLLED DOCUMENT A later revision of this specification may exist.	 <p style="font-size: x-small;">A member of The Marmon Group of companies</p>	Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F01458-X	Rev. ---