

**1. CONDUCTOR:**

- 1.1 Size and Material: 6 133/27 AWG tin-plated copper wire.
- 1.2 O.D.: .206" nom.

**2. INSULATION:**

- 2.1 Extruded silicone rubber.
- 2.2 Wall thickness: .152" nom
- 2.3 Marking on insulation: as per UL Standard.
- 2.4 O.D.: .510" nom.
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).
- 2.6 Talc powder applied on the insulation.

**3. PERFORMANCE:**

- 3.1 Voltage rating: 50 KVDC
- 3.2 Temperature rating: 150°C


**4. REFERENCE:**

- 4.1 UL Subject 758 (AWM), Style 10475.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.	This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Pierre Garand</i>	 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com				
		Date: March 5, 2012					
		Verified: <i>[Signature]</i>	Description: <b>XSF152Z6133/27-X</b>				
		Date: March 5, 2012					
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.			Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F01782-X</b>