			DATE	REV	ECN	DESCRIPTION
PRODUCTS	PECIFICATION		1/24/2004	А	3806	SPECIFICATION CREATED
INODUCIN						
Parent Number:	F14076-					
Description	14 41/30 BC MTW or AWM 1056/1275 TEW	VM 1056/1275 TEW				
	or AWM I A/B	TOLERANCE ±: +0.003/-0.002				
Stranding:	<u>41/30 BC LHL</u>			▼		MIN AVG WALL: 0.060
Style	UL: MTW or AWM 1056/1275 CSA: TEW or A	WMLA/B				
<u>Styte.</u>					1	MINIMUM WALL: <u>0.054</u>
Insulation:	<u>PVC</u>					
Print Legend: 14 AWG (2.08mm2) E51583 (PLANT ID CODE) (UL) MTW OR AWM 1056/1275 600V VW-1 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1						
<u>Voltage:</u>	<u>600V</u>					
_						
<u>Temperature:</u> Dry=105C, Wet=60C						
Notes:						
110105.						
This product complies with European Directive 2011/65/EU (RoHS 2)						
The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational						
purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of						
information contained herein or otherwise. This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to						Southwire
any party without written consent of Southwire Company, LLC.				SE SE		
<u>Customer Approval:</u>				1	Copperfield	
	<i>Nbr</i> (s):					
	Date:					5 W. North Street
Title:_		Name:				men, IN 46506 ne: 1-574-546-5115
					110	