

ToLWire.com & Vulkor.com

...≈ APPLIANCE DUAL-RATED WIRE≈...

## MTW MACHINE TOOL WIRE

(Hook-Up Wire)

Polyvinyl chloride (PVC) insulated wire manufactured to UL & CSA standards.

### APPLICATIONS:

Internal wiring for panels, meters, appliances, motors and transformers, electronic and lighting equipment, machine tool wire, where a medium wall insulation is required.

Multi-rated to UL 1015, UL 1230 and UL1032 1000Volt where applicable.

Also available UL 1032, UL 1335 & BC-5W2 rating.

CSA, TEW, AWM 1 A/B, VW-1 and FT1 rated. RoHS compliant.

### MTW/UL 1015 TEW Bare or Tinned Copper 105°C 600Volts

Product	#CU/MFT	Stranding	Wall Thickness	Minimum Order
MTW/1015-20-10-B	3.09	10/30	2/64	50M
MTW/1015-20-10-T	3.09	10/30	2/64	50M
MTW/1015-18-16-B	4.94	16/30	2/64	25M
MTW/1015-18-16-T	4.94	16/30	2/64	25M
MTW/1015-18-41-B	5.06	41/34	2/64	25M
MTW/1015-16-19-B	8.02	19/0117	2/64	25M
MTW/1015-16-26-B	8.03	26/30	2/64	25M
MTW/1015-16-26-T	8.03	26/30	2/64	25M
MTW/1015-14-19-B	12.70	19/0147	2/64	25M
MTW/1015-14-41-B	12.66	41/30	2/64	25M
MTW/1015-14-41-T	12.66	41/30	2/64	25M
MTW/1015-12-19-B	20.15	19/0185	2/64	25M
MTW/1015-12-65-B	20.80	65/30	2/64	25M
MTW/1015-12-65-T	20.80	65/30	2/64	25M

800-776-9223 (Ohio)

800-684-7823 (Texas)

MTW/1015-10-105-B	32.50	105/30	2/64	25M
MTW/1015-10-105-T	32.50	105/30	2/64	25M
MTW/1015-10-19-B	32.80	19/0234	2/64	25M
MTW/1028-8-19-B	50.96	19/0295	3/64	25M

**MTW/UL 1283 TEW Bare or Tinned Copper 105°C 600Volts**

Also available in tinned stranding.

Class K Stranding available in all cables bare or tinned.

Also rated BC-5W2 & UL 10269, 60H thru 4/0.

Meets or exceeds SAE J1127 in 6->4/0.

Product	Stranding	Wall Thickness	Minimum Order
MTW/1283-6-19-B	19/.0368	4/64	25M
MTW/1283-6-133-B	133x27	4/64	15M
MTW/1283-4-133-B	7x19x25	4/64	15M
MTW/1283-2-133-B	19x7x23	4/64	15M

**MTW/UL 1284 TEW Bare or Tinned Copper 105°C 600Volts**

Product	Stranding	Wall Thickness	Minimum Order
MTW/1284-1-133-B	19x7x.0249	5/64	20M
MTW/1284-1-266-B	19x14x25	5/64	15M
MTW/1284-1/0-133-B	19x7x.0282	5/64	15M
MTW/1284-2/0-133-B	19x7x.0315	5/64	10M
MTW/1284-3/0-266-B	19x14x.0249	5/64	10M
MTW/1284-4/0-266-B	19x14x.0282	5/64	5M

Minimum order requirement reflects quantity per color, per release.

Different color quantities may be combined to determine pricing with solid colors treated separately

**800-776-9223 (Ohio)    800-684-7823 (Texas)**