



**ATLAS WIRE CORPORATION**  
9525 RIVER STREET  
SCHILLER PARK, IL 60176  
(847) 678-1210  
(847) 678-1281 FAX  
www.atlaswirecorp.com



ATLAS WIRE CORPORATION  
REGISTERED TO ISO9001:2000  
CERTIFICATE NO. A4894

## MATERIAL SPECIFICATION SHEET

**#26 7/34 PREBOND .010" PVC**  
**RoHS COMPLIANT**  
**UL AWM Style 1061 300v 80c VW1**  
**CSA AWM I A/B 300v 80c FT1**

<b>CONDUCTOR:</b>	#26 7/34 PREBOND 1/3" LAY	
	NOMINAL O.D.	.019"
	APPROXIMATE CIRCULAR MILL AREA	279
	WEIGHT PER THOUSAND FEET	1.0#
	BASIC SPECIFICATION	ASTM B-470 TYPE II
<b>PVC:</b>	TEMPERATURE RATING	80c
	VOLTAGE RATING	300
	ELONGATION	240% AVERAGE
	SPECIFIC GRAVITY	1.30
	DUROMETER (SHORE)	63 (D)
	TENSILE STRENGTH	3500 PSI
	SPARK TESTED	5,700 VOLTS
	FINISHED O.D.	.039"
	WEIGHT PER THOUSAND FEET	1.55#
<b>USE:</b>	INTERNAL WIRING IN ELECTRIC BOOKKEEPING, ACCOUNTING, TIME RECORDING MACHINES, OR ELECTRONIC EQUIPMENT IF WITHIN A CHASIS OR PROTECTED FROM MECHANICAL INJURY.	

info@atlaswirecorp.com