



ATLAS WIRE CORPORATION
9525 RIVER STREET
SCHILLER PARK, IL 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



ATLAS WIRE CORPORATION
REGISTERED TO ISO9001:2000
CERTIFICATE NO. A4894

MATERIAL SPECIFICATION SHEET

#26 7/34 TOPCOAT .010" PVC
RoHS COMPLIANT
UL AWM Style 1061 300v 80c VW1
CSA AWM I A/B 300v 80c FT1

CONDUCTOR:	#26 7/34 TOPCOAT 1/3" LAY	
	NOMINAL O.D.	.019"
	APPROXIMATE CIRCULAR MILL AREA	279
	WEIGHT PER THOUSAND FEET	1.0#
	BASIC SPECIFICATION	ASTM B-470 TYPE I
PVC:	TEMPERATURE RATING	80c
	VOLTAGE RATING	300
	ELONGATION	240% AVERAGE
	SPECIFIC GRAVITY	1.30
	DUROMETER (SHORE)	63 (D)
	TENSILE STRENGTH	3500 PSI
	SPARK TESTED	5,700 VOLTS
	FINISHED O.D.	.039"
	WEIGHT PER THOUSAND FEET	1.55#
USE:	INTERNAL WIRING IN ELECTRIC BOOKKEEPING, ACCOUNTING, TIME RECORDING MACHINES, OR ELECTRONIC EQUIPMENT IF WITHIN A CHASIS OR PROTECTED FROM MECHANICAL INJURY.	

info@atlaswirecorp.com