



ATLAS WIRE CORPORATION
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



ATLAS WIRE CORPORATION
REGISTERED TO ISO 9001
CERTIFICATE NO. A4894

MATERIAL SPECIFICATION SHEET

#26 7/34 TINNED COPPER .010" PVC
RoHS COMPLIANT
AWM STYLE 1061 80c-300v VW-1
CSA AWM 80c-300v I A/B FT-1 SR PVC

CONDUCTOR:	#26 7/34 TINNED COPPER 3/8" CONCENTRIC	
	NOMINAL O.D.	.019"
	APPROXIMATE CIRCULAR MILL AREA	279
	WEIGHT PER THOUSAND FEET	0.9#
	BASIC SPECIFICATION	ASTM B-8 ASTM B-286
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	300v
	ELONGATION	300% AVERAGE
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	60 (D)
	TENSILE STRENGTH	3,210 PSI
	OXYGEN INDEX	28
	BRITTLE POINT	-8c
	SPARK TESTED	3,500 VOLTS
	FINISHED O.D.	.039"
	WEIGHT PER THOUSAND FEET	1.448#
USE:	INTERNAL WIRING OF ELECTRIC BOOKEEPING, ACCOUNTING, TIME RECORDING MACHINES OR ELECTRONIC EQUIPMENT IF WITHIN A CHASSIS OR PROTECTED FROM MECHANICAL INJURY.	

Info@atlaswirecorp.com

Revision 11/04/09