Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

\$

9978 Hook-up/Lead - UL AWM Style 1061

For more Information please call

1-800-Belden1



General Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

hysical Characteristics (Overall)	
Conductor AWG:	
# Conductors AWG Stranding Conductor Material	
1 30 Solid TC - Tinned Copper	
Total Number of Conductors:	1
nsulation	
Insulation Material:	
Insulation Material Wall Thickness (in.) PVC - Polyvinyl Chloride .010	
Overall Insulation Overall Cable	
Overall Nominal Diameter:	0.030 in.
echanical Characteristics (Overall)	
Bulk Cable Weight:	0.700 lbs/1000 ft.
pplicable Specifications and Agency Compli	iance (Overall)
Applicable Standards & Environmental Programs	
UL Rating:	300 V RMS, 80°C
UL Type:	AWM 1061
CSA Rating:	300 V RMS, 80°C
CSA Type:	AWM I, A/B
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Flame Test	
UL Flame Test:	VW-1
UL Flame Test: CSA Flame Test:	VW-1 FT1

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9978 001100	100 FT	0.100 LB	BROWN		30 SOL PVC BRN
9978 002100	100 FT	0.100 LB	RED		30 SOL PVC RED
9978 0021000	1,000 FT	1.000 LB	RED		30 SOL PVC RED
9978 003100	100 FT	0.100 LB	ORANGE		30 SOL PVC ORG
9978 0031000	1,000 FT	1.000 LB	ORANGE		30 SOL PVC ORG

Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

9978 Hook-up/Lead - UL AWM Style 1061

9978 004100	100 FT	0.100 LB	YELLOW	30 SOL PVC YEL
9978 0041000	1,000 FT	1.000 LB	YELLOW	30 SOL PVC YEL
9978 005100	100 FT	0.100 LB	GREEN, DARK	30 SOL PVC GRN
9978 0051000	1,000 FT	1.000 LB	GREEN, DARK	30 SOL PVC GRN
9978 007100	100 FT	0.100 LB	VIOLET	30 SOL PVC VIO
9978 0071000	1,000 FT	1.000 LB	VIOLET	30 SOL PVC VIO
9978 008100	100 FT	0.100 LB	GRAY	30 SOL PVC GRY
9978 009100	100 FT	0.100 LB	WHITE	30 SOL PVC WHT
9978 0091000	1,000 FT	1.000 LB	WHITE	30 SOL PVC WHT
9978 010100	100 FT	0.100 LB	BLACK	30 SOL PVC BLK
9978 0101000	1,000 FT	1.000 LB	BLACK	30 SOL PVC BLK
9978 013100	100 FT	0.100 LB	BLUE, DARK	30 SOL PVC DBLU
9978 0131000	1,000 FT	1.000 LB	BLUE, DARK	30 SOL PVC DBLU

Revision Number: 1 Revision Date: 08-16-2013

© 2015 Belden, Inc All Rights Reserved.

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU ROHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure is designed only as general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden belcares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.