Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



9987 Hook-up/Lead - UL AWM Style 1061

For more Information please call

1-800-Belden1



General Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

Physical Characteristics (Overall)

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	30	7x38	TC - Tinned Copper

Total Number of Conductors:

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.254

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.813 mm

Mechanical Characteristics (Overall)

Bulk Cable Weight: 1.191 Kg/Km

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating:	300 V RMS, 80°C
UL Type:	AWM 1061
CSA Rating:	300 V RMS, 80°C
CSA Type:	AWM I, A/B
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
me Test	
UL Flame Test:	VW-1
CSA Flame Test:	FT1

Plenum (Y/N): No

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9987 0021000	1,000 FT	1.000 LB	RED		30 STR PVC RED
9987 0071000	1,000 FT	1.000 LB	VIOLET		30 STR PVC VIO
9987 009100	100 FT	0.100 LB	WHITE		30 STR PVC WHT
9987 0091000	1,000 FT	1.000 LB	WHITE		30 STR PVC WHT
9987 010100	100 FT	0.100 LB	BLACK		30 STR PVC BLK

Page 1 of 2 11-05-2015

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



9987 Hook-up/Lead - UL AWM Style 1061

9987 0101000	1,000 FT	1.000 LB	BLACK	30 STR PVC BLK

Revision Number: 1 Revision Date: 08-16-2013

© 2015 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

product. ´
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Page 2 of 2 11-05-2015