

## Technical data sheet

PVC electronic cables · unshielded

### LÜTZE ELECTRONIC LiYY

Unshielded electronic cable UL recognized



#### Identification

Type LIYY 4×0,25  
Part No. [108614](#)

#### Product version

Datasheet version 00

#### Use/Application/Properties

- Application
- In all areas of electronics, measuring, monitoring and regulation technologies
  - In low voltage switchgear, communications engineering
  - In dry and damp rooms
  - For flexible application for free movement and without tensile loading
- Properties
- Minimal cable diameter through thin-walled PVC conductor insulation according to UL
  - Outer jacket special-PVC Class 43 according to UL
  - Very good oil resistance
  - Largely resistant to acids and bases
  - Silicone free

#### Construction

Description ELETRONIC LiYY  
Number of conductors/cross-section 4×0.25  
Number of conductors 4  
Cross-section, metric 0.25 mm<sup>2</sup>  
Jacket material Special PVC  
Jacket color grey similar to RAL 7001  
Outer Ø 4.8 mm  
Outer Ø 0.19 inch  
Tolerance ±0.2 mm  
Weight 3.3 kg/100 m

#### United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk

#### Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt  
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)  
www.luetze.de • info@luetze.de

08.03.2023 • Subject to technical modification

Part No. [108614](#) • Datasheet version: 00

page 1 of 3



SYSTEMATIC TECHNOLOGY

## Technical data sheet

### PVC electronic cables · unshielded

---

Separating agent	Talcum
Weight	22.2 Lbs/Mft
Cu-Index	1 kg/100 m
Cu-Index	6.7 Lbs/Mft

---

#### Construction Element 1

---

Element construction	4×0.25
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 5 Finely stranded DIN VDE 0295 Class 5
Conductor marking	Color coded
Conductor marking standard	DIN 47100
Conductor insulation	Special PVC

---

#### Overall construction

---

Overall stranding	layered construction
Jacket characteristics	Flame-retardant Oil resistant acid-resistant alkali-resistant Silicone-free

---

#### Technical data

---

Rated voltage	300 V
Test voltage type	AC 2000 V
Temperature according to UL	80 °C
Temperature range moving	-10 °C ... +70 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	12×D
Minimum bending radius fixed	5×D

---

#### Technical Data Element 1

---

Element construction	4×0.25
Insulation resistance at 20 °C	≥20 MΩ×km
Operating capacitance wire-wire	approx.90 pF/m

---

#### Certifications/Standards

---

Certifications	cURus
UL style	AWM 2464
Conformity	CE RoHS REACH

---

## Technical data sheet

### PVC electronic cables · unshielded

---

Burning behavior according to IEC 60332-1  
DIN EN 60332-1-2  
VDE 0482 322-1-2  
UL 1581 part VW-1 Flame Test  
UL FT1

---

#### General

---

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU