HellermannTyton

MK9P



Article Number: 110-09101

Mark 9 Pneumatic - Handle Air Supply Connection, includes tool and quick connect fittings.

RoHS

Download spec sheet

Base Data

Local Order Number	МК9Р
Туре	МК9Р
Color	Black (BK)
Features and Benefits	The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in demanding environments. It is ideally designed to apply heavy-duty ties (T50-T250), clamp and button head ties.
	Like the MK7P, HellermannTyton's MK9P incorporates the next level of ergonomic improvement with its low weight, comfortable grip and easy trigger depression. Very durable, the pneumatic MK9P features adjustable, easy to read tension settings. Lock-out features are available.
	The MK9P is available with lower air attachment (standard) or can be ordered with an upper air attachment.
Product Description	The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in demanding environments. It is ideally designed to apply heavy-duty ties (T50-T250), clamp and button head ties.
Short Description	Mark 9 Pneumatic - Handle Air Supply Connection, includes tool and quick connect fittings.

Product Dimensions

Air Attachment	lower air connection
Air Pressure Bar (max.)	6
Air Pressure Bar (min.)	3
Air Supply	non lubricated / lubricated
Recommended Cable Ties	
	CTT20 thru CTT175 Series EI-TY Series
	Button Head Series
Cycle Time	2 strokes per second
Number of cycles	100000
Air Pressure PSI	90
Tension Setting Tools	Adjustable
Cable Tie Width Max. (Imperial)	0.5 "
Cable Tie Width Max. (Metric)	12.7 mm
Pawl Travel Stroke (metric)	3.175 cm
Pawl Travel Stroke (imperial)	1.25 "
Power Supply	Dry or Lubricated Air
Tension Force	Adjustable

Logistics and Packaging

Quantity Per	carton
Package Quantity	1
Package Quantity (Metric)	1
Carton Quantity	1
Weight (imperial)	32 oz
Weight (Metric)	0.91 kg

Material and Specifications

ROHS Compliant Yes

© HellermannTyton 2015