

111-00732



Article Number: 111-00732

High Temp Cable Tie, 7.9" Long, 50lb Tensile Strength, ETFE, Blue, 100/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 111-00732

**Type** T50R

**Color** Blue (BU)

- Features and Benefits**
- ETFE cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure.
  - Inside serrations allows for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** High Temp Cable Tie, 7.9" Long, 50lb Tensile Strength, ETFE, Blue, 100/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 222.3 N

**Length L (Imperial)** 7.9 "

**Length L (Metric)** 201 mm

**Width W (Imperial)** 0.19 "

**Width W (Metric)** 4.7 mm

**Bundle Diameter Min. (Imperial)** 0.2 "

**Bundle Diameter Min. (Metric)** 5.0 mm

**Bundle Diameter Max. (Imperial)** 2.0 "

**Bundle Diameter Max. (Metric)** 50.0 mm

**Thickness T (Imperial)** 0.06 "

**Cable Tie Head Height (Metric)** 6 mm

**Cable Tie Head Length (Metric)** 9 mm

**Cable Tie Head Width (Metric)** 8.8 mm

**Cable Tie Head Length (Imperial)** 0.35 "

**Cable Tie Head Width (Imperial)** 0.33 "  
**Thickness T (Metric)** 1.5 mm

## Logistics and Packaging

---

**Quantity Per** bag  
**Package Quantity (Metric)** 100 Pieces  
**Carton Quantity** 5000  
**Weight (Metric)** 1.3 kg

## Material and Specifications

---

**Material** Ethylentetrafluoroethylene - (E/TFE)  
**Material Shortcut** E/TFE  
**Flammability** UL94 V0  
**Operating Temperature** -112°F to +338°F (-80°C to +170°C)  
**ROHS compliant (Article 4 - 1)** Yes  
**Certification/Specification** Det Norske Veritas  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes