

## T50SL6.NN6P

Article Number: 111-85469

Wing Push Mount Tie, 6.5" Long, 50lb Tensile, PA66, Natural, 500/bag



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T50SL6.NN6P

**Type** T50SL6

**Color** Natural (NA)

**Features and Benefits**

- Wing design helps stabilize the tie in high vibration applications
- Includes a ladder type strap as opposed to a conventional serrated strap; providing the benefit of being extra flexible.
- Design of tie provides low insertion and high extraction force.

**Product Description** Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.

**Fixation Method (FF)** Arrowhead

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Wing Push Mount Tie, 6.5" Long, 50lb Tensile, PA66, Natural, 500/bag

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225 N

**Length L (Imperial)** 6.5 "

**Length L (Metric)** 165 mm

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.6 mm

**Width W2 (Imperial)** 0.73 "

**Width W2 (Metric)** 18.5 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 1.3 "

**Bundle Diameter Max. (Metric)** 34.0 mm

**Disc Diameter (Imperial)** 0.73 "

**Disc Diameter (Metric)** 18.5 mm

**Panel Thickness Max. (Imperial)** 0.1 "

**Panel Thickness Min. (Imperial)** 0.02 "

**Mounting Hole Diameter D (Imperial)** 0.25 - 0.3 "

**Mounting Hole Diameter D (Metric)** 6.3 - 7.5 mm  
**Mounting Hole Diameter D Min. (Imperial)** 0.25 "  
**Mounting Hole Diameter D Max. (Imperial)** 0.3 "  
**Thickness T (Imperial)** 0.05 "  
**Mounting Hole Diameter D Max. (Metric)** 7.5 mm  
**Mounting Hole Diameter D Min. (Metric)** 6.3 mm  
**Thickness T (Metric)** 1.2 mm

## Logistics and Packaging

---

**Quantity Per** bag  
**Package Quantity (Metric)** 500  
**Carton Quantity** 4000

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)  
**Material Shortcut** PA66  
**Flammability** UL94 V2  
**Operating Temperature** -40°F to +185°F (-40°C to +85°C)  
**ROHS compliant (Article 4 - 1)** Yes