

111-12300



Article Number: 111-12300

Description: Wide-Strap Cable Tie, 9.1"L, 0.375"-2.25" Bundle Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg

Base Data	Local Order Number	111-12300
	Type	WSS
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> <li>• Wide strap is designed to minimize pinching of soft hoses and convoluted tubing.</li> <li>• Low-profile head with clamping rails provide compact bundling with a full circumferential compression around bundles.</li> <li>• Clamping rails on the bottom of head to increase grip on round bundles.</li> <li>• Wider and thinner strap design increases flexibility, provides low insertion and minimizes pinching of bundles.</li> <li>• Bent tail allows for quick insertion into head or mounts.</li> </ul>
	Quantity Per	bag
	Product Description	The Heavy Duty Wide-Strap Cable Tie was designed to minimize the pinching of soft bundles and the potential of lateral movement along the bundle. The low-profile head and underside clamping rails increase the grip around the bundle and provide a better fit than traditional cable ties. These are used primarily in the trucking and heavy equipment industries, but can be used in a wide variety of applications where strength is needed.
	GLOBAL PART NAME (auto set)	WSS-PA66HIRHSUV-BK
	Short Description	Wide-Strap Cable Tie, 9.1"L, 0.375"-2.25" Bundle Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg
	Product Dimensions	
Minimum Tensile Strength (Imperial)	120.0lbs	
Minimum Tensile Strength (Metric)	535.0N	
Length L (Imperial)	9.1"	
Length L (Metric)	231.0mm	
Fixation Method	None	
Identification Plate Position	none	
Releasable Closure	No	
Tie Closure	plastic pawl	
Variant	Inside Serrated	
Width W (Imperial)	0.5"	

111-12300



Product Dimensions	Width W (Metric)	12.7mm
	Bundle Diameter Min. (Imperial)	0.375"
	Bundle Diameter Min. (Metric)	9.7mm
	Bundle Diameter Max. (Imperial)	2.25"
	Bundle Diameter Max. (Metric)	58.4mm
	Thickness T (Imperial)	0.055"
	Cable Tie Head Length (Imperial)	0.393"
	Cable Tie Head Width (Imperial)	0.78"
	Thickness T (Metric)	1.4mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	300
	Package Quantity (Metric)	300
	Customs Number(Schedule B)	3926909987
	Weight (Metric)	0.0042kg
	Weight (imperial)	0.0092lbs