

112-52115



Article Number: 112-52115

Description: Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HSUV, Black, 1000/pkg

Base Data	Local Order Number	CTT60R0HSUVM4
	Type	CTT60R
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • Heat and UV stabilized cable ties provide excellent resistance to high heat and UV exposures. • Head design contains clamping rails to provide full circumferential compression around bundles. • Bent tail allows for quick insertion into head.
	Quantity Per	bag
	Brand Family	CTT
	Product Description	The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
	GLOBAL PART NAME (auto set)	CTT60R-PA66HSUV-BK
	Short Description	Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HSUV, Black, 1000/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		265.0N
Length L (Imperial)		8.0"
Length L (Metric)		205.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.19"
Width W (Metric)		4.7mm

112-52115



Product Dimensions	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	1.8"
	Bundle Diameter Max. (Metric)	45.0mm
	Thickness T (Metric)	1.2mm
Material and Specifications		
	Material	Polyamide 6.6 heat and UV stabilized (PA66HSUV)
	Material Shortcut	PA66HSUV
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +257°F (-40°C to +125°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.0027lbs
	Weight (Metric)	0.0012kg