

CONDUCTOR

Conductor: 18 19/30 Silver Plated Copper
Conductor diameter: 0.0475 nominal

INSULATION

Extruded PTFE in accordance with UL AWM Style 1180
Insulation diameter: 0.079 nominal
Insulation color: Green

MARKING

In accordance with CSA CAN/CSA-C22-2 No. 210.2-M90 Section 7.7.1
Legend: "E171212 (<R)U AWM STYLE 1180 300V 200C LL107298 CSA AWM I A/B 300V 200C FT1"
Insulation diameter: 0.079 nominal

SPIRAL STRIPE

Color: Yellow
Insulation diameter: 0.079 nominal

SURFACE ETCH

Sodium etch insulation surface
Insulation diameter: 0.079 nominal

QUALITY

UL Style 1180 300 volts, 200 degrees C
CSA AWM I A/B FT1 300 volts, 200 degrees C
UL Style 1180/CSA AWM Tagged
ROHS Compliant
REACH Compliant

Super-Temp		
Wire & Cable, Inc. 802-655-4211		
Drawn by: Jody Place	Date: 3/16/17	Revision:
Description: XU13 18 19/30 GREEN/YELLOW UL1180/CSA		
Super-Temp Part Number: SE0180-54		

Customer Approval
Approved by:

Date Approved: