

**Aerospace Part#:** 1195a26

**PLENUM CABLE**

**DESCRIPTION**

12 Conductors AWG 26/7x34 TC  
Unshield FEP/FEP Gray CL2P CMP

**PHYSICAL PROPERTIES**

**Conductors**

**Insulation**

# Conductors	AWG	Material	Material	Wall	Finished OD
12	26/7x34	Tinned Copper	FEP	.006"	.031"

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Gray	.010"	.149" Nom.	3" Lay on Cable

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	19.5 lbs / m	10 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage
UL Rated 300V Power Ltd.

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

Reach / RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Applications	Communications, Audio, Control, Instrumentation Remote, Signaling, Power-limited systems
Flame Test	NFPA 262 / FT6
NEC / (UL) Specification	CL2P / CMP
CEC / C (UL) Specification	CMP

**MISCELLANEOUS**

Markings: TYPE CL2P - TYPE CMP 26 AWG (UL), C(UL) FEP/FEP E130356 ROHS

Color Code: Black / Red / White / Green / Brown / Blue / Orange / Yellow / Purple / Gray / Pink / Tan /

**Contact Us For More Information**

**T:** 800.395.0200 **F:** 718.358.2522 **E:** sales@aerospacewire.com **W:** www.aerospacewire.com

**LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**

\* Specification subject to error and may change without notice