

1. CONDUCTOR:

- 1.1 Size and Material: 18 19/.0092" AWG silver-plated copper wire.
- 1.2 O.D.: .044" nom.

2. INSULATION:

- 2.1 Extruded PTFE.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .112" nom.
- 2.4 Color: black.

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C
- 3.3 Pull-off force (per BICC QS-129 test): 2.5 lbs min. for 3" of insulation




4. REFERENCE:

- 4.1 UL Subject 758 (AWM), Style 1199.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Garand</i> Date: January 17, 2008		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com							
1511									Verified: <i>David L...</i> Date: January 17, 2008		Description: <h2 style="margin: 0;">IEWC 101797</h2>							
									Size: A Scale: --- Page: 1 of 1						Code Ident. No: 57104		Specification No.: F00135-S	
UNCONTROLLED DOCUMENT A later revision of this specification may exist.									 A member of The Marmon Group of companies									