



REFERENCE ONLY IF PRINTED



NOTES:

1. STRIP ONE END OF WIRE AND TIN WITH LEAD FREE, ROHS SOLDER OR TOP COAT PROCESS.
2. WIRE LENGTH TOLERANCES ARE +/- .25"
3. STRIPPED END TOLERANCES ARE +/- .03"

NOTE: COMPONENT MUST MEET ROHS 2 DIRECTIVE INCLUDING THE USE OF LEAD FREE SOLDER IF APPLICABLE

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES. TOLERANCE: SEE NOTES		NAME	DATE	 <p>DITEK Surge Protection 1720 Starkey Road Largo, FL 33771 1-800-753-2345 www.ditekurgeprotection.com</p>
	DRAWN BY	K. PFEUFFER	7/19/21	
	VP OF ENGINEERING	DAVE GATTIS	7/19/21	
	DESIGN ENGINEER	C. COMPTON	7/19/21	
	MANUFACTURING ENGINEER	K. PFEUFFER	7/19/21	
	QA	L. DISANZA	7/7/21	
UPDATED BY	K. PFEUFFER	2/21/23		
TITLE: 18" AWG BLACK WIRE, 300V OR 600V INSULATION, UL RECOGNIZED				
120-180 VARIOUS		MATERIAL: 12 AWG STRANDED WIRE		SIZE DRAWING NUMBER: REV B MDW-120180 2
PART NUMBER	USED ON	FINISH: N/A		
APPLICATION		DO NOT SCALE DRAWING		SCALE: 1:1 WEIGHT: SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DITEK CORP. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF DITEK CORP IS PROHIBITED