


REFERENCE ONLY IF PRINTED



NOTES:

1. STRIP ONE END OF WIRE AND TIN WITH LEAD FREE, ROHS SOLDER OR TOP COAT PROCESS.
2. WIRE LENGTH TOLERANCES ARE +/- .25"
3. STRIPPED END TOLERANCES ARE +/- .03"

NOTE: COMPONENT MUST MEET ROHS 2 DIRECTIVE INCLUDING THE USE OF LEAD FREE SOLDER IF APPLICABLE

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
ALL DIMENSIONS ARE IN INCHES.		DRAWN BY	K. PFEUFFER 7/19/21
TOLERANCE: SEE NOTES		VP OF ENGINEERING	DAVE GATTIS 7/19/21
		DESIGN ENGINEER	C. COMPTON 7/19/21
		MANUFACTURING ENGINEER	K. PFEUFFER 7/19/21
		QA	L. DISANZA 7/19/21
		UPDATED BY	K. PFEUFFER 2/21/23



DITEK Surge Protection
 1720 Starkey Road
 Largo, FL 33771
 1-800-753-2345
www.diteksurgeprotection.com

TITLE: 18" AWG GREEN WIRE,
 300V OR 600V INSULATION,
 UL RECOGNIZED

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DITEK CORP. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF DITEK CORP IS PROHIBITED

120-182	VARIOUS	MATERIAL: 12 AWG STRANDED WIRE	COMMENTS:	SIZE	DRAWING NUMBER:	REV
PART NUMBER	USED ON	FINISH: N/A		B	MDW-120182	2
APPLICATION		DO NOT SCALE DRAWING	SCALE: 1:1	WEIGHT:	SHEET 1 OF 1	