



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 74-323

CONSTRUCTION SPECIFICATIONS

Description	AWM 2C 12 AWG Unshielded
Conductor	12 AWG 65 Strand Tinned Copper
Conductor Diameter	0.093"
Insulation Type	Flame Retardant PVC
Insulation Thickness	0.030"
Conductor Identification	Black, White
Ripcord	Polyester Ripcord included under the cable jacket
Jacket	Flame Retardant PVC
Jacket Thickness	0.030" (minimum average)
Overall Cable Diameter	0.379"
Jacket Print	CSA AWM II A/B105C 600V FT4 LL67097 RU AWM STYLE 2463 80C E111002 ROHS (work order)

ELECTRICALS

Voltage	600V
Conductor Resistance	1.72 Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	*CSA C22.2 No. 210.2, Appliance Wiring Material Products
UL Recognized	*UL 758, Appliance Wiring Materials
Flame Test Rating	CSA FT4
Temperature Rating	80C; STYLE 2463 / 105C; AWM II
ROHS	Compliant
Cable Weight	113.06 kg/km
Copper Content	58.84 kg/km
Max Pull Tension	65 kgs
Min Bending Radius	4.75 inches (installed)
Min Installation Temp	-20C

Rev. 000

21-Jan-11