Technical Data Sheet Communication Cables





2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

PART NUMBER:	25227B
DESCRIPTION:	12/2 Stranded bare copper conductors, unshielded with an overall jacket.
NEC RATING:	CL2P, NEC Article 725
APPROVALS:	(UL) or (ETL)us Listed
APPLICATION:	Indoor within ducts, plenums, and other spaces used for environmental air for (Intercom Systems, Security Systems, Sound, Audio, Background Music)

Construction Parameters:

Conductor Stranding Insulation Material Insulation Thickness Number of Conductors Shield Drain Jacket Material Jacket Thickness Overall Cable Diameter Approximate Cable Weight Flame Rating

Electrical & Environmental Properties:

Temperature Rating Operating Voltage Max.Capacitance Between Conductors @ 1 KHz DC Resistance per Conductor @ 20deg C Insulation Colors Jacket Color RoHS Compliant

Mechanical Properties:

Max. Recommended Pull Tension Min. Bend Radius (Install)

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Cold Environment Precautions: Due to the nature of PVC Compounds to become non-pliable when stored or handled in ambient temperatures of 32 deg. F or less, we recommend the following:

"Prior to installation, condition the cable for at least 24 hours at room temperature to provide the best flex properties for ease of installation." 12 AWG Bare Copper 19x25 Polymer Alloy 0.010" Nom. 2 None Flexible Plenum 0.015" Nom. 0.221" Nom. 54 Lbs/1M' Nom. NFPA 262 Flame Test

-10°C To +60°C 150 V RMS 36 pf/ft Nom. 1.7 Ohms/1M' Nom. Black, Red Gray Yes

146 lbs 2.5"

Standard Lengths are 1000ft. The Jacket is sequentially footmarked. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.