

Home Products Cross Reference Value-Added Services Request Information

Credit Application

About Us

Contact Us



Search

Your source for the latest wire & cable products

Need help? Call us toll-free: 800-526-2269

sales@olympicwire.com

Olympic P/N 2894T : Twisted Pair, Shielded, Low Voltage, Plenum, Control Cable

No of Conductors	2
Conductor Size	12 AWG
Stranding	19/25, Bare Copper
Insulation	Low Smoke PVC
Shielding	Aluminum Mylar with Stranded Tinned Copper Drain Wire
Jacket	Low Smoke PVC, White
Nom OD	0.260 in
UL Style	CMP/CL3P/FPLP
UL Flame Test	NFPA 262
CSA Flame Test	FT-6
Nominal Capacitance (Capacitance between conductors)	70 pF/ft
Nominal Capacitance (Capacitance Between One Conductor and Other Conductors Connected to Shield)	135 pF/ft
Voltage	300 V
Color Code	White, Black
RoHS Compliant	Yes
Compliance	

Request Information (/contact/request-information/?topic=Olympic P/N 2894T : Twisted Pair, Shielded, Low Voltage, Plenum, Control Cable)
Datasheet (pdf) (http://info.olympicwire.com/information/product/2894T)
Email Page (http://info.olympicwire.com/information/product/2894T)

Product Specifications and Website Information are Subject to Change Without Notice.

[Color Code Charts \(HTML\)](#)
[Cable Selector Guide \(PDF\)](#)

[Technical Data \(PDF\)](#)

[RoHS Compliance Statement \(PDF\)](#)

[Reach Position Statement \(PDF\)](#)

[Limited Warranty – Disclaimer – Limitation of Remedies \(PDF\)](#)

[Privacy Policy \(HTML\)](#)

Copyright © 2016 · Olympic Wire · Crafted by spheres.net