



For more Information
please call

1-800-Belden1



General Description:

Commercial Audio Cable, Rated-CL3, 4-12 AWG highly flexible stranded bare copper conductors with PVC insulation, PVC jacket with ripcord

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
4	12	65x30	Bare High-Conductivity ETP Copper

Total Number of Conductors: 4

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.508

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.559

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Lay Length & Direction:

Length (mm)	Twists (twist/m)
126.9995	7.8744

Overall Cabling Color Code Chart:

Color
Black
White
Red
Green

Overall Nominal Diameter: 9.271 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 174.119 Kg/Km

Max. Recommended Pulling Tension: 1503.492 N

Min. Bend Radius/Minor Axis: 92.075 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CL3

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

METRIC MEASUREMENT VERSION

5002UP Multi-Conductor - Commercial Audio Systems

EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/m)
0.52496

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
104.992

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
5.11836

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Current
21 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5002UP D15500	500 FT	61.000 LB	BLUE		4 #12 PVC FRPVC
5002UP 005500	500 FT	61.000 LB	GREEN, DARK		4 #12 PVC FRPVC
5002UP 0081000	1,000 FT	122.000 LB	GRAY		4 #12 PVC FRPVC
5002UP 008500	500 FT	61.000 LB	GRAY		4 #12 PVC FRPVC
5002UP 0091000	1,000 FT	122.000 LB	WHITE		4 #12 PVC FRPVC
5002UP 009500	500 FT	61.000 LB	WHITE		4 #12 PVC FRPVC
5002UP 0101000	1,000 FT	122.000 LB	BLACK		4 #12 PVC FRPVC
5002UP 010500	500 FT	61.000 LB	BLACK		4 #12 PVC FRPVC

Revision Number: 2 Revision Date: 04-15-2014

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.