

Rev:	Change:	By:	Date:
C	General Format	SKW	3/18/2015



Construction:

OD (In.)

1 Conductor:	18 19/30 Silver Plated Copper (SPC)	0.047" Nom.
Insulation:	Extruded Polytetrafluorethylene (PTFE)	0.068" Nom.
Color:	Per Order	
Surface Print:	"UL AWM STYLE 1213 18 AWG TFE 105C VW-1 HBR-S CSA AWM I A/B 150C 150V FT1"	

Physical Characteristics

1 Weight per 1000':	7.8	Lbs. nom.
2 Operating temperature range:	105 °C for UL	150 °C for CSA
3 RoHS compliance:	Complies with RoHS (Directive 2002/95/EC)	
4 UL/CSA Rating:	UL1213/CSA	

Harbour Industries
 4744 Shelburne Rd., Shelburne, VT 05482
 PH: 802-985-3311 Fax: 802-985-0726 www.harbourind.com



Drawn By: <i>S.K. Wooster</i>	This drawing contains proprietary information and is issued in strict confidence and shall not be copied, reproduced, transmitted or disclosed to any third party either wholly or in part without prior written approval of Harbour Industries . All copies outside of the Harbour Industries CAD system are Uncontrolled .		
Approved By: <i>M.T. Piner</i>	Part Number:	Rev:	Sheet:
Date: 5/3/96	J1064-* *Designates color	C	1 of 1
Scale: None	Drawing Name:	Drawing Number:	
	XU10 18 19/30 SPC PTFE UL1213/CSA	050396_2	