

126-00069

Article Number: 126-00069

Wing Push Mount Tie, 6.0" Long, 50lb Tensile, PA66, Natural, 500/bag

HellermannTyton



Download spec sheet

## Base Data

Local Order Number 126-00069

Type T50SSFM

Color Natural (NA)

- Features and Benefits**
- Wing design helps stabilize the tie in high vibration applications.
  - Includes a ladder type strap as opposed to a conventional serrated strap; giving the benefit of being extra flexible.
  - Wing design provides low insertion and high extraction force.

**Product Description** Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.

**Short Description** Wing Push Mount Tie, 6.0" Long, 50lb Tensile, PA66, Natural, 500/bag

## Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 6.3 "

Length L (Metric) 160.0 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Width W2 (Metric) 14.7 mm

Height H (Imperial) 0.2 "

Height H (Metric) 5.6 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Panel Thickness Max. (Imperial) 0.12 "

Panel Thickness Max. (Metric) 3.0 mm

Panel Thickness Min. (Imperial) 0.03 "

Panel Thickness Min. (Metric) 0.7 mm

**Mounting Hole Diameter D (Metric)** 6.0 - 6.6 mm

**Mounting Hole Diameter D Max.** 6.6 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 6.0 mm

## Logistics and Packaging

---

**Quantity Per** bag

**Package Quantity (Metric)** 500

**Carton Quantity** 5000

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes