

126-00081

Article Number: 126-00081

Arrowhead Cable Tie, 6" Long, 50lb Tensile Strength, 6.5mm Round Hole, PA66HS Black, 500/Pkg

HellermannTyton



Download drawing



Download spec sheet

Base Data

Local Order Number 126-00081

Type T50SOSKSFT65E

Color Black (BK)

- Features and Benefits**
- Dome provides a tight, rattle-free installation.
 - Outside serrated strap has ribs designed for convoluted tubing.
 - Dome acts as a seal to keep out dust and liquid.

Product Description HellermannTyton's low profile push mount design provides an overall shortened length which assists in limiting protrusion on the opposing side of application surfaces. The rounded tip of the mount allows for a smoother surface in case of contact with surrounding components or human touch during service.

Short Description Arrowhead Cable Tie, 6" Long, 50lb Tensile Strength, 6.5mm Round Hole, PA66HS Black, 500/Pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 40.0 lbs

Minimum Tensile Strength (Metric) 180 N

Length L (Imperial) 6.2 "

Length L (Metric) 156.0 mm

Fixation Method Arrowhead (Small Mount)

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.38 "

Bundle Diameter Max. (Metric) 35.0 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.051 "

Panel Thickness Max. (Metric) 1.3 mm

Panel Thickness Min. (Imperial) 0.027 "

Panel Thickness Min. (Metric) 0.7 mm

Mounting Hole Diameter D (Imperial) 0.25-0.26 "

Mounting Hole Diameter D (Metric) 6.3 - 6.7 mm

Mounting Hole Diameter D Min. (Imperial) 0.248 "

Mounting Hole Diameter D Max. (Imperial) 0.264 "

Mounting Hole Diameter D Max. (Metric) 6.7 mm
6.3 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Carton Quantity 5000 Pieces

Weight (Metric) 1.3 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes