

126-00086

Article Number: 126-00086

Domed Low Profile Mount Ties, 6.2" Long, Mounting Hole Diameter .25" - .26", PA66HS, Black, 500/pkg

HellermannTyton



Download drawing



Download spec sheet

Base Data

Local Order Number 126-00086

Type T50SOSKSFT6.5S2-E

Color Black (BK)

- Features and Benefits**
- Dome provides a tight, rattle-free installation.
 - Outside serrated strap has ribs designed for convoluted tubing.
 - Dome acts as a seal to keep out dust and liquid.

Product Description HellermannTyton's low profile push mount design provides an overall shortened length which assists in limiting protrusion on the opposing side of application surfaces. The rounded tip of the mount allows for a smoother surface in case of contact with surrounding components or human touch during service.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Domed Low Profile Mount Ties, 6.2" Long, Mounting Hole Diameter .25" - .26", PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 6.2 "

Length L (Metric) 157.5 mm

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.58 "

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.09 "

Panel Thickness Min. (Imperial) 0.07 "

Mounting Hole Diameter D (Imperial) 0.25 - 0.26 "

Mounting Hole Diameter D (Metric) 6.3 - 6.7 mm

Mounting Hole Diameter D Min. (Imperial) 0.248 "
Mounting Hole Diameter D Max. (Imperial) 0.264 "
Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. (Metric) 6.7 mm
Mounting Hole Diameter D Min. (Metric) 6.3 mm
Thickness T (Metric) 1.3 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 500 Pieces
Carton Quantity 5000 Pieces
Weight (Metric) 1.3 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut PA66HS
Flammability UL94 V2
Operating Temperature -40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1) Yes