

126-00116

Article Number: 126-00116

Wing Push Mount Tie, 8" Long, 50lb Tensile, PA66HS, Black, 500/bag



Download drawing



Download spec sheet

Base Data

Local Order Number 126-00116

Type T50RSFM

Color Black (BK)

- Features and Benefits**
- Wing design helps stabilize the tie in high vibration applications.
 - Includes a ladder type strap as opposed to a conventional serrated strap which provides the benefit of being extra flexible.
 - Tie is releasable and reusable giving additional use options.

Product Description Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Wing Push Mount Tie, 8" Long, 50lb Tensile, PA66HS, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 8.0 "

Length L (Metric) 200.0 mm

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.22 "

Height H (Metric) 5.6 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.8 "

Bundle Diameter Max. (Metric) 45.0 mm

Panel Thickness Max. (Imperial) 0.12 "

Panel Thickness Min. (Imperial) 0.04 "

Mounting Hole Diameter D (Imperial) 0.24 -0.26 "

Mounting Hole Diameter D (Metric) 6.0 - 6.6 mm

Mounting Hole Diameter D Min. 0.24 "

(Imperial) Mounting Hole Diameter D Max. 0.26 "
(Imperial)

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. 6.6 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 6.0 mm

Thickness T (Metric) 1.3 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Carton Quantity 4000

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS compliant (Article 4 - 1) Yes