

126-02300

Article Number: 126-02300

Arrowhead Push Tie, Panel Thickness .24" - .26", 7.0" Long, 50lb Tensile, PA66HIRHS, Natural, 500/bag

HellermannTyton



Download drawing



Download spec sheet

Base Data

Local Order Number 126-02300

Type T50SST5

Color Natural (NA)

- Features and Benefits**
- Arrowhead design makes installation by hand quick and easy without the need for tools.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete.
 - Design provides low insertion and high extraction force.

Product Description Arrowhead Push Ties secure fast and easy, while providing a disc feature to minimize the ingress of dust, dirt, and water. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.

Short Description Arrowhead Push Tie, Panel Thickness .24" - .26", 7.0" Long, 50lb Tensile, PA66HIRHS, Natural, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 7.0 "

Length L (Metric) 170.0 mm

Fixation Method Arrowhead

Identification Plate Position none

Length of Fir Tree 8.0 mm

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.4 "

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.2 "

Bundle Diameter Max. (Metric) 31.0 mm

Disc Diameter (Imperial) 0.64 "

Disc Diameter (Metric) 16.2 mm

Panel Thickness Max. (Imperial) 0.06 "

Panel Thickness Max. (Metric) 1.5 mm

Panel Thickness Min. (Imperial) 0.03 "

Panel Thickness Min. (Metric)	0.7 mm		
Mounting Hole Diameter D (Imperial)	0.24 - 0.26 "		
Mounting Hole Diameter D (Metric)	6.1 - 6.5 mm		
Mounting Hole Diameter D Min. (Imperial)	0.24 "	Mounting Hole Diameter D Max. (Imperial)	0.255 "
			Thickness T (Imperial) 0.05 "
Mounting Hole Diameter D Max. (Metric)	6.5 mm	Mounting Hole Diameter D Min. (Metric)	6.1 mm
Thickness T (Metric)	1.2 mm		

Logistics and Packaging

Quantity Per	pieces
Package Quantity (Metric)	1000 Pieces
Carton Quantity	5000 Pieces
Weight (Metric)	1.2 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes