

126-03100



Article Number: 126-03100

Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag



Download drawing



Download spec sheet

Base Data

Local Order Number 126-03100

Type T50SOSSFT6.5E-MDL

Color Green (GN)

Features and Benefits This tie has an arrowhead design of fixing which offers a positive, low push-in force and a high pull-out force. When combined with the optional foam rubber seal it offers additional protection against the ingress of moisture or dirt.

Product Description Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 200 N

Length L (Imperial) 6.3 "

Length L (Metric) 158.8 mm

Length of Fir Tree 7.0 mm

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.67 "

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.2 "

Bundle Diameter Max. (Metric) 30.0 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.07 "

Panel Thickness Min. (Imperial) 0.02 "

Mounting Hole Diameter D (Imperial) 0.25 - 0.26 "

Mounting Hole Diameter D Min. (Imperial) 0.25 "
Mounting Hole Diameter D Max. (Imperial) 0.26 "
Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. (Metric) 6.7 mm
Mounting Hole Diameter D Min. (Metric) 6.3 mm
Thickness T (Metric) 1.3 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 500 Pieces
Carton Quantity 3000 Pieces
Weight (Metric) 2 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut PA66HS
Flammability UL94 V2
Operating Temperature -40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1) Yes