

Aerospace Part#: 1268/19w

CONTROL CABLE

DESCRIPTION

2 Conductors AWG 20/19x32 TC
Overall Braid Shield FEP/FEP White 600V 200C

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
2	20/19x32	Tinned Copper	FEP	.010"	.058"

Outer Braid Material

Layer 1 Type	Material	AWG	Coverage
Overall Braid Shield	Tinned Copper	36	90%

Outer Jacket Material

Cablings

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	White	.015"	.169" Nom.	2" Lay on Cable with Clear Mylar

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	24.7 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
Rated 600 Volts

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Reach / RoHS Compliant	YES
------------------------	-----

MISCELLANEOUS

Color: Black / White /
Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice