

**Aerospace Part#:** 1268/19y604

**CONTROL CABLE**

**DESCRIPTION**

2 Conductors AWG 20/19x32 TC  
Overall Braid Shield Fiberglass Filler FEP/FEP Yellow

**PHYSICAL PROPERTIES**

**Conductors**

**Insulation**

# Conductors	AWG	Material	Material	Wall	Finished OD
2	20/19x32	Tinned Copper	FEP	.009"	.056"

**Outer Braid Material**

Layer 1 Type	Material	AWG
Overall Braid Shield	Tinned Copper	36

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Yellow	.025"	.190" Nom.	1.5" Lay on Pair with 2 TFE Coated Fiberglass Filler + .001"Clear Mylar Binder

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	32.3 lbs / m	10 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage
Rated 300 Volts

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

Reach / RoHS Compliant	YES
Suitability	Indoor, Wet location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid

**MISCELLANEOUS**

Color Black / White /  
Code:

**Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

**LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**

\* Specification subject to error and may change without notice