

Aerospace Part#: 1281KW

PLENUM CABLE

DESCRIPTION

2 Conductors AWG 22/7x30 TC
Unshielded White CL2P CMP 150C

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
2	22/7x30	Tinned Copper	FEP	.006"	.042"

Outer Jacket Material

Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
Fluoropolymer	White	.010"	.104" Nom.	1" Lay on Cable

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -40C to 150C	8.0 lbs / m	15 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
UL Rated 300V Power Ltd.

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Reach / RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Applications	Communications, Audio, Control, Instrumentation Remote, Signaling, Power-limited systems
Flame Test	NFPA 262 / FT6
NEC / (UL) Specification	CL2P / CMP
CEC / C (UL) Specification	CMP

MISCELLANEOUS

Markings: TYPE CL2P - TYPE CMP 22 AWG (UL), C(UL) 150C E130356 ROHS

Color Code: Black / Red /

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice