

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: MTW/1283-6-133-B
Spec Revision Level: A8

Description: 6 AWG MTW/THW-2 AWM UL STYLE
1283/1232/10269 105 Deg C 600V/1000V,
VW-1, PVC Cable

Conductor (Stranding): 133 x 27 AWG Bare Copper, UL
Conductor OD (Nom) 0.180 inches
Max. Lay Length: 3.0 inch Lay
Min Wall Thickness: 0.054 inches
Nom. Wall Thickness: 0.060 inches
Min. O.D: 0.302 inches
Nom. O. D: 0.314 inches
Circular Mils (CMA): 25715 (Min)
Temperature Rating: Minus 40 DegC to 105 DegC
Surface Print: 6 AWG (UL) MTW /THHW/THW-2/BC-5W2/AWM
1232/1283/1346 600V 105C OR 10269 1000V VW-1
E116277 CSA TEW OR AWM I A/B 105C 600V FT1
W 75 O-- LL 55996 SAE J1127 SGT

This Product is RoHS Compliant

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A	Packard: N/A
UL : AWM 1283/1232 / 10269 Std 758/83 & CSA			Other: N/A

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Product Engineering Manager)

Date: 5-30-2019