



Southwire[®]
 WE DELIVER POWER... RESPONSIBLY[®]

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
 Waukegan, IL 60085
 Toll-Free (800) 323-9355
 Fax: (847) 689-1192

PART NUMBER: 50152
DESCRIPTION: 400 MCM MTW THHW AWM CABLE
CONSTRUCTION: This cable consists of one bare copper conductor with PVC insulation..
APPROVALS: UL Standards 1063, 83 & 758; CSA C22.2 No. 210.
APPLICATION: Machine Tool Wire, Thermoplastic Insulated Wire and Appliance Wiring Material

Construction Parameters:

Conductor	400 MCM Bare Copper
Stranding	259 Strands
Insulation Material	PVC
Insulation Thickness	0.100" Nom.
Insulated Conductor Diameter	0.985" Nom.
Approximate Cable Weight	1443.4 Lbs/1M' Nom.
Flame Rating	VW-1 or FT1 Vertical Flame Test

Electrical Properties:

Temperature Rating	-20°C to 90°C (105C - AWM)
Operating Voltage	600V Max (MTW), 1000V Max (AWM 10269)
DC Resistance per Conductor @ 20°C	0.030 Ohms/1M' Nom.
Ampacity per NFPA 79 Table 12.5.1* for 75°C	412 Amps
Ampacity per NFPA 70 (NEC) Table 310-17 for THHW	615 Amps

Insulation Color Black (Other colors available - consult factory)

Legend (Surface Ink Jet Print) 400 MCM (203mm²) E137733 (UL) MTW OR THHW FOR CT USE OR AWM STYLES 1284 & 1339 600V OR 10269 1000V SUN RES VW-1 -- 156016 CSA AWM I A/B 105C 600V FT1

This product complies with European Directive 2002/95/EC (RoHS)

* Ampacities converted to 105C ampacity using 60C cable temperature and 30C ambient from NFPA 79 Table 12.5.1.

The customer will accept all factory lengths and +/- 10 percent of total order requested.

Material is not returnable and purchase order is non-cancelable after production has been started or special materials have been ordered.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Customer Name _____ Date Signed _____

Customer Approval _____

Specification Issue Date: January 7, 2013