

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: MTW/1284-4/0-2109-T
Spec Revision Level: A9

Description: 4/0 AWG MTW AWM UL STYLE 1284 , Tinned Copper
2109 Strands, 105 DegC 600V, PVC Jacket Cable

Conductor (Stranding): 19 x 111 x 30 AWG Tinned Copper, UL
Rope Construction

Conductor OD (Nom) 0.592 inches
Max. Lay Length: 5.1 inch Lay
Min Avg Wall Thickness: 0.080 inches
Nom. O. D: 0.762 inches
Min O.D : 0.750 inches
Paper Separator : No Paper Separator
Circular Mils (CMA): 207368 (Min)
Surface Print: 4/0 AWG MTW OR THW OR AWM 1284 VW-1 (UL) E
86321 600V 105C CSA TEW AWM I A LL49526 “ FOR
CT USE “

This Product is RoHS Compliant

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
Packard: N/A	Other: UL / CSA C22.2#127-2009 Sub 758 / UL 1284/UL1063	

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By:

Mir Hussain (Corporate Quality Engineer)

Dated: 7-20-2016